



**Cook with
greater power.**

FRYER



Model	RFA-227	RFA-327
Features	<ul style="list-style-type: none"> • 22 liter Gas Fryer • Digital one-touch • Auto control system • Easy oil draining through the bottom of fryer • Auto temperature control (50°C-220°C) • Safety device for over heating • Front oil discharge function • Timer setting function • Fryer basket included • Filter adopted for oil recycling 	<ul style="list-style-type: none"> • 31 liter gas fryer • Digital one-touch • Auto control system • Easy oil draining through the bottom of fryer • Auto temperature control (50°C-220°C) • Safety device for over heating • Front oil discharge function • Timer setting function • Fryer basket included • Filter adopted for oil recycling
Performance	Gas Connection : 9.5 Gas Consumption : Δ LPG : 1.22 Kg/h Δ LNG : 15,500 Kcal/h	Gas Connection : 9.5 Gas Consumption : Δ LPG : 1.36 Kg/h Δ LNG : 17,200 Kcal/h
Dimensions	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 450(W) x 615(D) x 1.000(H) - mm • Weight : 39 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 600(W) x 615(D) x 1.000(H) - mm • Weight : 47 Kg

Rinnai

Customer Care

Jl. Raya Perjuangan No.21,
Komp. Ruko Sastra Graha No. 11-13, Kebon Jeruk, Jakarta 11530
Layanan Konsumen 0804-1-889-889





COMMERCIAL PRODUCT CATALOG

Rinnai



Designed
for your tastes.

GAS RICE COOKER DOUBLE & TRIPLE DECK



Model	RRA-106	RRA-156
Features	<ul style="list-style-type: none"> • Insulating plate • Self diagnosis function • Flame failure safety device • Various cooking functions • Easy selection • Saving 10% gas consumption • For 100 people 	<ul style="list-style-type: none"> • Insulating plate • Self diagnosis function • Flame failure safety device • Various cooking functions • Easy selection • Saving 10% gas consumption • For 150 people
Performance	Gas Connection : 3/4" (20A) Gas Consumption : Δ LPG : 1.58 Kg/h Δ LNG : 19,000 Kcal/h	Gas Connection : 3/4" (20A) Gas Consumption : Δ LPG : 2.42 Kg/h Δ LNG : 29,000 Kcal/h
Dimensions	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 700(W) x 727(D) x 1.036(H) - mm • Weight : 100 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 700(W) x 727(D) x 1.397(H) - mm • Weight : 150 Kg

GAS ROASTER SERIES



Model	R-92WSV	RG-440F	RG-640F
Features	<ul style="list-style-type: none"> • Auto ignition by Piezo • Control knob convenient • SUS body adopted (easy cleaning and durability) • 2-steps heating power control • Ceramic infrared burner (upper side) • Safety device 	<ul style="list-style-type: none"> • Auto ignition by Piezo • Control knob in front for convenient • SUS body adopted (easy cleaning and durability) • 2-steps heating power control • Ceramic infrared burner (upper side) • Cooking easy by movable grill mesh 	<ul style="list-style-type: none"> • Auto ignition by Piezo • Control knob in front for convenient • SUS body adopted (easy cleaning and durability) • 2-steps heating power control • Ceramic infrared burner (upper side) • Cooking easy by movable grill mesh
Performance	Gas Connection : 9.5 Gas Consumption : △ LPG : 0.32 Kg/h △ LNG : 4,000 Kcal/h	Gas Connection : ϕ9.5(HOSE END) Gas Consumption : △ LPG : 0.7 Kg/h △ LNG : 8,400 Kcal/h	Gas Connection : ϕ9.5(HOSE END) Gas Consumption : △ LPG : 1.0 Kg/h △ LNG : 12,000 Kcal/h
Dimensions	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 622(W) x 282(D) x 233(H) - mm • Weight : 11 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH): 570(W) x 630(D) x 275(H) - mm • Weight : 18 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH): 770(W) x 630(D) x 275(H) - mm • Weight : 18 Kg



Model	RSB-923N	RSB-926N
Features	<ul style="list-style-type: none"> • Auto ignition by Piezo • Infrared light heating • 4 level rack control • Various cooking modes • Clean cooking with stainless steel mesh 	<ul style="list-style-type: none"> • Auto ignition by Piezo • Infrared light heating • 4 level rack control • Various cooking modes • Clean cooking with stainless steel mesh
Performance	Gas Connection : 9.5 Gas Consumption : △ LPG : 0.5 Kg/h △ LNG : 6,200 Kcal/h	Gas Connection : 9.5 Gas Consumption : △ LPG : 1.0 Kg/h △ LNG : 12,000 Kcal/h
Dimensions	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH): 773(W) x 400(D) x 568(H) - mm • Weight : 26,9 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH): 1,287(W) x 400(D) x 568(H) - mm • Weight : 42.4 Kg

GAS GRIDDLE SERIES



Model	RSB-450H	RSB-903H
Features	<ul style="list-style-type: none"> • Table sitting type • Temperature adjust function (160°C-280°C) • 3-side oil protection guard • Gas automatic cut-off safety device • Attachment of ignition checking window 	<ul style="list-style-type: none"> • Auto ignition by Piezo • Auto gas cut-off safety device • 3-side oil protection guard • Stainless steel of front side • 3 steps heating power control • Installed lower rack for cooking ware • Dripped pan installed
Performance	Gas Connection : 9.5 Gas Consumption : Δ LPG : 0.34 Kg/h Δ LNG : 4,100 Kcal/h	Gas Connection : 1.2" (15A) Gas Consumption : Δ LPG : 0.8 Kg/h Δ LNG : 9,500 Kcal/h
Dimensions	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH): 450(W) x 600(D) x 360(H) - mm • Weight : 22 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH): 900(W) x 750(D) x 850(H) - mm • Weight : 72 Kg

GAS RANGE SERIES



Model	RLT-120	RSB-320L	RSB-420L
Features	<ul style="list-style-type: none"> • 2-step power heating control • Auto ignition by Piezo • SUS mesh thermal efficiency • High caloric double burner • Separable safety backguard • Durable stainless steel 	<ul style="list-style-type: none"> • Auto ignition by Piezo • 2-step power heating control • High caloric double burner • Durable stainless steel • Separable top plate for easy cleaning • Installed lower rack for cookware 	<ul style="list-style-type: none"> • Auto ignition by Piezo • 2-steps heating power control • High caloric double burner (Big/Mid) • Durable stainless steel • Separative top plate for easy cleaning • Installed lower rack for cooking ware
Performance	Gas Connection : 1 1/4" (32A) Gas Consumption : Δ LPG : 3.32 Kg/h Δ LNG : 39,600 Kcal/h	Gas Connection : 1" (25A) Gas Consumption : Δ LPG : 2.00 Kg/h Δ LNG : 23,500 Kcal/h	Gas Connection : 1" (25A) Gas Consumption : Δ LPG : 3.2 Kg/h Δ LNG : 36,500 Kcal/h
Dimensions	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 1200(W) x 711(D) x 620(H) - mm • Weight : 94 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 900(W) x 600(D) x 795(H) - mm • Weight : 73 Kg 	<ul style="list-style-type: none"> • Appliance Dimensions (WxDxH) : 1200(W) x 600(D) x 795(H) - mm • Weight : 90 Kg